

DWR105-OG-C-15W



DWR105-OG-C-15W.png

Source	LED Bridgelux
Connection	Wire
Gr. Power	15W ±5%
Input Voltage	AC85-277V
Driver	Lifud
Control (standard)	Not dim.
Dimming option	Triac dim.; 0-10V dim.; DALI
Beam Angle (°)	13/24/38/60
CCT (Kelvins)	2700°K; 3000°K; 4000°K; 5000°K; 6500°K; 5700°K
Lumens	1500
Luminaire efficiency	100Lm/W
CRI (standard)	>80Ra
for option	>90Ra; >97Ra
Fixture Color	White; Black
Cover	Stripped
Dimensions	Dia 105*64mm (hole 90)
Protection Rating	IP40 / IK07
Electrical Class	Class II
Lifetime	>50.000h
Warranty	3 Years

Standard Packing Details


Unit Volum (CBM)	0,00127
Unit GW (kg)	0,55
Qty per carton	50

Other

Reflector in White, Black, Silver or Gold; Cree, Citizen or Osram LED; Tridonic, Philips or Osram Driver; 5 years warranty for option

DWR105-OG-C-15W

Sizes drawing




DWR105-OG-C-15W.drw

in mm

Illumination Diagram

1500Lm with 24° beam



DWR105-OG-C-15W.lux

